



IKR 361 C, high current, ceramic coated, DN 40 ISO-KF





Similar Image

IKR 361 C, high current, ceramic coated, DN 40 ISO-KF

- For vacuum processes in high- and ultra high vacuum
- Very low external magnetic field
- Display range $1 \cdot 10^{-9}$ to $1 \cdot 10^{-2}$ hPa
- Cold cathode (inverted magnetron)
- Rugged and dependable
- Insensitive to air ingress
- Without elastomer seal
- For measuring corrosive media
- Maximum pressure refers to inert gases and temperatures of less than $< 55^\circ\text{C}$

Technical Data	IKR 361 C, high current, ceramic coated, DN 40 ISO-KF
Accuracy: 10^{-8} - 10^{-2} hPa	$\pm 30\%$
Anode	Molybdenum
Bakeout temperature	Elektronics removed, $\leq 150^\circ\text{C}$ Elektronics removed, $\leq 302^\circ\text{F}$ Elektronics removed, $\leq 423\text{ K}$
Feature	Corrosion resistant
Feedthrough	Glass, ceramic coated
Flange	Stainless steel 1.4435
Materials in contact with media	Stainless steel 1.4435, 1.4310, Molybdenum, glass, aluminium oxide ceramic
Measurement range max.	0.01 hPa $7.5 \cdot 10^{-3}$ Torr 0.01 mbar
Measurement range min.	$1 \cdot 10^{-8}$ hPa $7.5 \cdot 10^{-9}$ Torr $1 \cdot 10^{-8}$ mbar
Method of measurement	Cold Cathode
Nominal diameter	DN 40 ISO-KF
Output signal: Minimum load	10 k Ω
Output signal: Pressure range	2.5 - 8.5 V
Output signal: Sensor error below	0.5 V
Pressure max.	10,000 hPa 7,500 Torr 10,000 mbar
Repeatability: 10^{-8} - 10^{-2} hPa	$\pm 5\%$
Sensor cable length max.	$\leq 300\text{ m}$ (1 mm ² /wire)
Supply: Power consumption max.	$\leq 2\text{ W}$
Supply: Voltage	14.5-30 V
Temperature: Operating	$5-55^\circ\text{C}$ $41-131^\circ\text{F}$ $278-328\text{ K}$
Temperature: Storage	$-40-70^\circ\text{C}$ $-40-158^\circ\text{F}$ $233-343\text{ K}$
Volume	20.9 cm ³
Weight	$< 320\text{ g}$

Order number

IKR 361 C

PT T01 150 011

Accessories

Accessory for ActiveLine gauges and controllers

Mating connector

B 4707 283 MA

Sensor cable, 3 m

PT 448 250 -T