



HiPace® 700 with TC 400, DN 160 CF-F, G 1/4"






Illustration only

HiPace® 700 with TC 400, DN 160 CF-F, G ¼"


- Compact yet powerful turbopump with a pumping speed of up to 685 l/s for N₂
- Maximum vacuum performance with minimum power consumption
- For installation in any orientation
- TC 400 integrated electronic drive unit
- Integrated, powerful cooling system

Characteristics



HiPace® 700

Dimensions



HiPace® 700

Technical Data	HiPace® 700 with TC 400, DN 160 CF-F, G ¼"
Electronic drive unit	TC 400
Type of electronic drive unit installation	Integrated electronic drive unit
Position of power supply pack	External power supply pack
Cooling method	Water
Pumping speed	1998 – 2466 m³/h
Pumping speed category	2520 m³/h
Pumping speed for He	655 l/s
Pumping speed for N ₂	685 l/s
Vacuum range min	5 · 10 ⁻¹⁰ hPa
Vacuum range max	5 · 10 ⁻¹⁰ hPa
I/O interfaces	RS-485, Remote
Cooling water temperature	15 – 35 °C
Interfaces, extended	Profibus DeviceNet E74
Venting connection	G 1/8"
Bearing	Hybrid
Cooling method, optional	Air (forced convection)
Current max.	8.4 A
Mounting orientation	Arbitrary
Temperature: Storage, max	55 °C
Temperature: Storage, min	-20 °C
Pumping speed for Ar	665 l/s
Pumping speed for H ₂	555 l/s
Emission sound pressure level (EN ISO 2151)	≤50 dB(A)
Gas throughput at final rotation speed for H ₂	14 hPa·l/s
Gas throughput at final rotation speed for He	20 hPa·l/s
Run-up time	2 min
Compression ratio for Ar	1 · 10 ¹¹
Compression ratio for H ₂	4 · 10 ⁵
Compression ratio for He	3 · 10 ⁷
Compression ratio for N ₂	1 · 10 ¹¹
Gas throughput at final rotation speed for N ₂	6.5 hPa·l/s
Gas throughput at final rotation speed for Ar	3.5 hPa·l/s
Fore-vacuum max. for N ₂	11 hPa 8.25 Torr 11 mbar
Pumping speed for He	655 l/s
Pumping speed for N ₂	685 l/s

Rotation speed $\pm 2\%$	49,200 rpm 49,200 min ⁻¹
Pumping speed for Ar	665 l/s
Pumping speed for H ₂	555 l/s
Compression ratio for N ₂	$1 \cdot 10^{11}$
Compression ratio for H ₂	$4 \cdot 10^5$
Compression ratio for He	$3 \cdot 10^7$
Compression ratio for Ar	$1 \cdot 10^{11}$
Permissible radial magnetic field max.	6 mT
Fore-vacuum max. for N ₂	11 hPa
Cooling water flow	100 l/h
Power consumption max.	420 W
03 Vacuum range	High Vacuum Ultra-high Vacuum
Connection flange	DN 160 CF-F / DN 25 ISO-KF G 1/4" Thread
Rotation speed variable	60 – 100 %
Rotation speed $\pm 2\%$	49,200 rpm
Weight	17.4 kg
Connection flange (in)	DN 160 CF-F
Connection flange (out)	DN 25 ISO-KF G 1/4"

Order number	HiPace® 700 with TC 400, DN 160 CF-F, G 1/4"
HiPace® 700 with TC 400, DN 160 CF-F, G 1/4"	2000236409



伯东企业（上海）有限公司
HAKUTO ENTERPRISES (SHANGHAI) LTD.
TEL: (86) 21-5046 3511

上海伯东 -- 您理想的真空合作伙伴！

伯东公司成立于 1953 年，外企上市企业，全球范围内有一千七百名员工，集团年营业额约为 100亿人民币。

伯东公司在国内主要城市：上海，北京，苏州，广州，深圳，成都及厦门设有营业据点。

上海伯东真空产品事业部已累计为超过 10,000 家企业提供真空服务


我们致力于追求高品质的服务，为您提供一流的服务及一流产品：

品质保障：国际知名品牌指定授权代理商，所有产品及部件保证 100% 原厂原装进口

现货交期快：部分产品有现货，下单立即发货（现货数量有限，实际情况请联系销售工程师）

卓越维修能力：伯东工程师拥有10年以上维修经验，且受国外专业培训，拥有完全的拆解，维修，校正能力。

完美服务质量：原装进口检测设备全方位寻找问题症结及全方面的性能测试，确保完美的服务质量



伯东企业（上海）有限公司 销售及售后服务中心

上海浦东新区新金桥路1888号36号楼7楼702室

电 话：+86-21-5046-3511 / 139-1883-7267

传 真：+86-21-5046-1490

官 网：<http://www.hakuto-vacuum.cn>

